



## Precision accessories MFG.CORP

0.75 Inch | 19.05 Millimeter x 1.125 Inch | 28.58  
Millimeter x 1.313 Inch | 33.35 Millimeter LINK  
BELT KLPSS212DC Pillow Block Bearings



KLPSS212DC Bearing 2D drawings and 3D CAD models

Bearing No. KLPSS212DC

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 0.331  |
| EAN                       | 0793699513189  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Thermoplastic  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/8 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | SG212EL  |
| Seals                     | Single Lip Contact   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Inch   |
| Other Features            | Single Row   Intermediate Duty   White Housing   Stainless Steel Insert   Closed End   Extended Inner Race |
| Long Description          | 2 Bolt Pillow Block; 3/4" Bore; 1-5/16" Base to Center   |



## Precision accessories MFG.CORP

|                               |   |
|-------------------------------|---|
|                               | Height; Set Screw Mount; Ball Bearing; Relubricatable; Thermoplastic; Single Lip Contact; Non-expansion |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a>   |
| Manufacturer Item Number      | KLPSS212DC  |
| Manufacturer Internal Number  | 0151318   |
| Weight / LBS                  | 1.5   |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| B                             | 1.313 Inch   33.35 Millimeter   |
| D                             | 1.125 Inch   28.58 Millimeter   |
| Nominal Bolt Center to Center | 3.8 Inch   97 Millimeter  |
| Actual Bolt Center to Center  | 3.8 Inch   96Millimeter   |
| d                             | 0.75 Inch   19.05 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |